


$$\triangle_2 \triangle_3 \quad \frac{KX}{(1)} \quad \frac{XX}{(2)} \quad \frac{T}{(3)} - \frac{H}{(4)}$$

- (1) KX:3.96mm KX Board To Board
(2) XX:No. Of Position/Per Row
(3) T:Female DIP Top Entry
(4) H:RoHS Compliant

Pin	A	B
02	3.96	8.06
03	7.92	12.02
04	11.88	15.98
05	15.84	19.94
06	19.80	23.90
07	23.76	27.86
08	27.72	31.82
09	31.68	35.78
10	35.64	39.74
11	39.60	43.70
12	43.56	47.66
13	47.52	51.62
14	51.48	55.58
15	55.44	59.54
16	59.40	63.50

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY EMILY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ⚠.X ±0.35 ⚠.XX ±0.10 ANG.		⚠A4 Modify Data		HZF	05/27/2022
PART No. KXXXT-H		CHECKED BY HZF				⚠A3 Modify Data		HZF	11/07/2014
DRAWING No. KXXXT-H		DRAWING BY HAO				⚠A2 Modify Data		HZF	08/20/2012
						⚠A1 Modify Data		HZF	12/18/2009
						⚠A0 NEW RELEASE			
SCALE	NONE	REV.	A4	UNIT mm		NO. REV.	REVISIONS	CHK	DATE