



△△ SPECIFICATION

Current Rating:1A
 Withstanding Voltage:500V(1 Minute)
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min. At 500V DC
 Operating Temperature:-40°C~+85°C
 Insulator:PBT+30%G.F.(UL94V-0)
 Contact:Brass,Gold Flash On Contact Area,
 Tin Plated On Solder Tails,Over Nickel
 Shell:Steel,Nickel Plated Front,Tin Plated Rear
 Nut:Brass,Nickel Plated
 RoHS Compliant

△ DS XX S J T - XX - H
 (1) (2) (3) (4) (5) (6) (7)

- (1) DS:D-SUB Solder Wire Type
- (2) XX:No. Of Position
- (3) S:Female
- (4) J:Rivet Front Jackscrew
- (5) T:Tray Packing
- (6) XX:Insulator Color
 Blank:Blue
 BK:Black
 WH:White
- (7) H:RoHS Compliant

Pin	A	B	C	D
09	16.33	24.99	30.81	19.20
15	24.80	33.32	39.20	27.70
25	38.38	47.04	53.04	41.10
37	54.84	63.50	69.40	57.30
50	52.20	61.00	67.00	55.10

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AUK AND SHALL NOT BE DISTRIBUTED, REPRODUCED, OR DISCLOSED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION OF AUK.

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY	APPROVED BY EMILY	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △.X ±0.38 .X* ±3* .XX ±0.25 .XX* ±1* .XXX ±0.05 .XXX* ±0.5
PART No. DSXXSJ-XX-H	CHECKED BY HZF	
DRAWING No. DSXXSJ-XX-H	DRAWING BY GAO	
SCALE NONE	REV. A2	

NO.	REV.	REVISIONS	CHK	DATE
△A2		Modify Data	HZF	11/14/2020
△A1		Modify P/N:DS15SJ-BK-H -->DSXXSJ-XX-H Add DS09SJ,DS25SJ-H,DS15SJ-H	HZF	08/05/2013
△A0		NEW RELEASE	HZF	10/22/2007